



G.PLAST S.R.L. a socio unico

Via Canova, 11 - 36053 Gambellara (VI) – Italy

VAT IT00678080243 – Rea VI-146095

Share capital 100.000 €

Phone: +39 (0)444 648963 - Email: info@gplast.it - www.gplast.it

PVC HEAVY CONE WITH CL 2 REFLECTIVE BANDS



TECHNICAL CHARACTERISTICS

	H 34 PVC CONE - S2202PVCPCCL2	H 34 PVC CONE - S2002PVCPCCL2
Height	34 cm	34 cm
Weight	0,90 kg	0,90 kg
Base dimension	22,5 x 22,5 cm	22,5 x 22,5 cm
Number of bands	1	2
Height of the bands	10,5 cm	5 cm
Material	Fluorescent orange soft PVC - CL2 Reflective band	Fluorescent orange soft PVC - CL2 Reflective band

The information provided herein reflects our current knowledge. We cannot assume any liability or claim for damages.
G.PLAST srl reserves the right to modify technical specifications and models without notice.



G.PLAST S.R.L. a socio unico

Via Canova, 11 - 36053 Gambellara (VI) – Italy

VAT IT00678080243 – Rea VI-146095

Share capital 100.000 €

Phone: +39 (0)444 648963 - Email: info@gplast.it - www.gplast.it

	H 54 PVC CONE - S2203PVCPCCL2	H 54 PVC CONE - S2003PVCPCCL2
Height	54 cm	54 cm
Weight	2,20 kg	2,20 kg
Base dimension	28,5 x 28,5 cm	28,5 x 28,5 cm
Number of bands	2	3
Height of the bands	10,5 cm	7 cm
Material	Fluorescent orange soft PVC - CL2 Reflective band	Fluorescent orange soft PVC - CL2 Reflective band

TECHNICAL CHARACTERISTICS OF THE CL2 REFLECTIVE BANDS

The CL1 reflective band is a flexible, highly reflective, weatherproof, self-adhesive film with excellent corrosion and solvent resistance. The retroreflective system consists of encapsulated catadioptric glass beads (corresponds to class RA 2, design B, formerly Type II). The reflective data and colours at daylight comply with the international specifications of this class such as EN 12899-1 (European Regulation), DIN 67520 and DIN 6171 (Germany), BS 873: Part 6 (Great Britain), NFP 98-520 (France), SN 640878 (Switzerland), ASTM D 4956 (US), JIS Z 9117 (Japan).

Table 1 – Specific coefficient of retroreflection R' in cd/lx/m2									
Observation angle	0,2°			0,33°			2°		
Entrance angle	5°	30°	40°	5°	30°	40°	5°	30°	40°
white (010)	250	150	110	180	100	95	4	2,4	1,4

Physical and Chemical Properties

Thickness* (without protective paper and adhesive): 210 micron

Temperature resistance**: adhered to aluminium, from -40° C to +82° C

Adhesive power* (FINAT-TM1 after 24h, stainless steel): 15 N/25 mm (film tear)

*average ** standard central European climate

The information provided herein reflects our current knowledge. We cannot assume any liability or claim for damages.
G.PLAST srl reserves the right to modify technical specifications and models without notice.



G.PLAST S.R.L. a socio unico

Via Canova, 11 - 36053 Gambellara (VI) – Italy

VAT IT00678080243 – Rea VI-146095

Share capital 100.000 €

Phone: +39 (0)444 648963 - Email: info@gplast.it - www.gplast.it

HOW TO USE

Traffic cones are used to delimit and highlight working areas, for maintenance operations, during the making of the horizontal road markings, to indicate areas affected by accidents, for temporary channeling, for temporary marking of opposite directions of traffic, and to limit temporary obstacles. They complement the use of appropriate vertical signs.

For more information on how to use them, please refer to the regulations in force in the country of use.

The cones are resistant to impacts and atmospheric agents.

The base of the cone is shaped to allow greater visibility and to reduce the risk of the cone rolling away after falling.

PACKAGING

CODE	PACKAGING	QTY/BOX	BOX/PALLET
S2202PVCPL2	box	15 pcs	24/27
S2002PVCPL2	box	15 pcs	24/27
S2203PVCPL2	box	5 pcs	24/28
S2003PVCPL2	box	5 pcs	24/28

The information provided herein reflects our current knowledge. We cannot assume any liability or claim for damages.
G.PLAST srl reserves the right to modify technical specifications and models without notice.