



G.PLAST S.R.L. a socio unico

Via Canova, 11 - 36053 Gambellara (VI) – Italy

VAT IT00678080243 – Rea VI-146095

Share capital 100.000 €

Phone: +39 (0)444 648963 - Email: info@gplast.it - www.gplast.it

“GP DRAGO” SAFETY HELMET



TECHNICAL CHARACTERISTICS

Product type	Safety helmet
PPE	III cat.
Certifications	EN397:2012 + A1:2012
Electric insulation	440 VAC
Shell material	PE HD “UV”
Manual size-adjustment material	PE LD
Automatic size-adjustment material	PP
Ratchet size-adjustment material	PA6
Head circumference	53-62 cm
Size-adjustment	Manual Automatic With ratchet
Ventilation	Not ventilated
Hooking points	6
Sweatband	Sponge and fabric sweatband
Thermal resistance	+50 °C / - 20°C

The information provided herein reflects our current knowledge. We cannot assume any liability or claim for damages.
G.PLAST srl reserves the right to modify technical specifications and models without notice.



G.PLAST S.R.L. a socio unico

Via Canova, 11 - 36053 Gambellara (VI) – Italy

VAT IT00678080243 – Rea VI-146095

Share capital 100.000 €

Phone: +39 (0)444 648963 - Email: info@gplast.it - www.gplast.it

Compatible or replacement accessories	Sweatband High Visibility Kit
Other features	Option to attach a logo sticker to the front of the helmet
Validity from production date	5 years
Available colors .XX	 YE  WH  RD

CLEANING AND MAINTENANCE

The helmet must be cleaned using a non-aggressive detergent and hot water (not exceeding a temperature of 50°C). Avoid contact with liquids or spray that contain solvents, acids, or alcohol, since they may reduce the sturdiness of the cap.

CHECK BEFORE USE

Prior to each use, the helmet must be checked to detect the presence of any cracks, cuts or other damage. If found, the helmet must be replaced. The elements that have been subjected to significant impact must be replaced even if they do not show visible sign of damage. Before wearing the helmet, always check that the straps are well fastened to their fastening points and that the helmet is well positioned when worn, so as to ensure impact-absorption. The helmet must not be used 5 years after the date of manufacture marked on it. This date must be read as follows: the two numbers in the middle indicate the year of manufacture while the arrow marks the month.

The information provided herein reflects our current knowledge. We cannot assume any liability or claim for damages.
G.PLAST srl reserves the right to modify technical specifications and models without notice.



G.PLAST S.R.L. a socio unico

Via Canova, 11 - 36053 Gambellara (VI) – Italy

VAT IT00678080243 – Rea VI-146095

Share capital 100.000 €

Phone: +39 (0)444 648963 - Email: info@gplast.it - www.gplast.it

STORAGE

Store the hard hat in a clean, dry location at normal room temperature in an uncontaminated area where it cannot be damaged.

OTHER INFORMATION

Do not alter, modify or tamper with this device - Do not use the helmet if it shows cracks or cuts
Do not apply paints on the helmet - The use of the helmet must be limited to industrial areas, building construction sites or roadway construction sites, as well as forestry, caves or mining applications. Do not use it for applications not listed above.

The manufacturer does not assume any liability for any unintended use of the PPE.

PACKAGING

CODE	DESCRIPTION	WEIGHT	QTY/BOX	BOX/PALLET
SH.9000.V01.XX	Inside in fabric and manual size-adjustment	325 gr	24 pcs	16/20
SH.9000.V03.XX	Inside in fabric and automatic size-adjustment	360 gr	24 pcs	16/20
SH.9000.V07.XX	Inside in fabric and ratchet size-adjustment	365 gr	24 pcs	16/20

The information provided herein reflects our current knowledge. We cannot assume any liability or claim for damages.
G.PLAST srl reserves the right to modify technical specifications and models without notice.